



WELL Pad

WELL Pad is an outdoor-ready, completely wireless, battery-powered rectangular RGBA LED wash light that provides excellent coverage of walls, and stages or landscapes and architectural elements from its wide beam and field angles. The unit's orientation can be manipulated thanks to a unique 90-degree rotation system from its base. It can be controlled via W-DMX or by an included IR remote; alternatively, it can be controlled manually from the OLED display on the fixture. Selectable PWM ensures that this completely wireless wash light is always camera-ready.

Coming Soon



At a Glance

- A completely wireless, IP65 rated, battery powered up-light with 96 single color (red, green, blue, and amber) LEDs that is controlled by W-DMX or IR remote
- Drop in case for easy storage and recharging of the battery
- Magnetic diffuser filter included
- 9 hours of operation at full output with a recharge time of 6 hours
- Built in automated programs recallable by IR, W-DMX or manually
- 90-degree rotation of the panel from the base for easy direction of light
- M12 threaded insert for easy clamp installation and a Kensington lock position for securing your investment
- IP65 rating for temporary outdoor usage

Specifications

Optical

- Light Source: 96 LEDs (24 red, 24 green, 24 blue, 24 amber) 1 to 3 W, (500 mA), 50,000 hours life expectancy
- Beam Angle (w/o filter): 22°
- Beam Angle (w/filter): 27°
- Field Angle (w/o filter): 38°
- Field Angle (w/filter): 51°
- Illuminance (w/o filter): 553 lux @ 5 m
- Illuminance (w/filter): 316 lux @ 5 m

Dynamic Effects

- Tilt: 90°
- Tilt Ranges: 0° to 90° tilt
- Color Macros: 5 macros
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

Construction / Physical

- Dimensions: 15.98 x 8.38 x 3.99 in (406 x 213 x 101.5 mm)
- Dimensions (charging case): 26.29 x 22.83 x 19 in (668 x 580 x 482.6 mm)
- Weight (single unit): 21.6 lb (9.8kg)
- Weight (charging case): 67.8 lb (30.8kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: W-DMX
- DMX Channels: 4, 6 or 10
- Modes/Personalities: 3 personalities (4Ch, 6Ch, 10Ch)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current (single unit charging): 120 W, 0.996 A @ 120 V, 60 Hz
- Power and Current (charging case): 480 W, 3.984 A @ 120 V, 60 Hz
- Power and Current (single unit charging): 135 W, 0.654 A @ 208 V, 60 Hz
- Power and Current (charging case): 540 W, 2.616 A @ 208 V, 60 Hz
- Power and Current (single unit charging): 137 W, 0.594 A @ 230 V, 50 Hz
- Power and Current (charging case): 548 W, 2.376 A @ 230 V, 50 Hz

Battery

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 6 hours
- Battery Life: (all on) 9 hours, (single LED) 13 hours
- Battery Power: 18.5 V, 26 Ah

Certifications / Qualifications

- CE
- IP Rating: IP65, temporary outdoor/wet use with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- WELL Pad X4
- Charging case
- IR remote
- (4) Diffusion filters
- powerCON power cable with Edison plug

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07